

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1.-7. (Canceled)

8. (Currently Amended) A wing mirror unit for a motor vehicle comprising:
a mirror foot;
a mirror housing connected to the mirror foot; and
an actuator;

wherein the mirror housing is adjustable with respect to the mirror foot between a folded orientation, in which the mirror housing substantially extends along said motor vehicle, and an unfolded orientation, in which the mirror housing is substantially oriented transversely to said motor vehicle; a pivot for the folded and unfolded orientations is provided outside the mirror foot and within the mirror housing; the actuator is configured to move adjacent surfaces of the mirror housing and the mirror foot transversely with respect to each other between a first position, in which the adjacent surfaces of the mirror housing and the mirror foot form a slit, and a second position, in which the adjacent surfaces abut each other.

9. (Previously presented) The wing mirror unit according to claim 8, wherein the actuator is configured to adjust the wing mirror unit in or near the unfolded orientation between the first position and the second position, such that during adjustment between the folded orientation and the unfolded orientation the wing mirror unit is substantially in the first position.

10. (Original) The wing mirror unit according to claim 8, wherein the mirror foot comprises a base pivot, around which the mirror housing, under action of the actuator, is pivotally arranged with respect to the mirror foot.

11. (Withdrawn) The wing mirror unit according to claim 10, wherein the adjacent surfaces of the mirror housing and the mirror foot form contact surfaces; the contact surfaces are located around the base pivot at a first distance; and the mirror foot and the mirror housing cooperate via at least one cam path assembly curvedly extending around the base pivot at a second, smaller distance.

12. (Withdrawn) The wing mirror unit according to claim 11, wherein the at least one cam path assembly comprises a cam provided on one of the mirror housing or the mirror foot, the cam engaging a cam path provided on the other.

13. (Withdrawn) The wing mirror unit according to claim 12, wherein the cam path includes a flat path part that, during folding and unfolding of the mirror housing with respect to the mirror foot, provides the slit between the contact surfaces.

14. (Withdrawn) The wing mirror unit according to claim 13, wherein a run-on surface in or about the unfolded orientation allows the contact surfaces to adjust between the first and the second position.

15. (Original) The wing mirror unit according to claim 8, wherein the actuator is a linear actuator.

16. (Previously presented) The wing mirror unit according to claim 15, wherein the adjacent surfaces of the mirror housing and the mirror foot form contact surfaces; and at least one of the contact surfaces is comprised of an elastic material.

17. (Original) The wing mirror unit according to claim 15, wherein the mirror foot and the mirror housing are translatably arranged with respect to each other, and the adjacent surfaces of the mirror housing and the mirror foot, in the second position, cooperate in a form-closed manner and, through translation in transverse direction with respect to said motor vehicle, are adjustable

between the first position and the second position.

18. (Original) The wing mirror unit according to claim 8, wherein the adjacent surfaces of the mirror housing and the mirror foot form contact surfaces; and at least one of a contact surfaces is comprised of an elastic material.

19. (Original) The wing mirror unit according to claim 18, wherein when the at least one contact surface is elastically deformed, the mirror housing can pivot with respect to the mirror foot.

20. (Currently Amended) A mirror unit for comprising:

a mirror foot;

a mirror housing connected to the mirror foot; and

an actuator pivotally connected to the mirror foot,

wherein a pivot for folding and unfolding the mirror housing relative to the mirror foot is provided outside the mirror foot and within the mirror housing; and the actuator is configured to move adjacent surfaces of the mirror housing and the mirror foot transversely with respect to each other between a first position, in which the adjacent surfaces of the mirror housing and the mirror foot form a slit, and a second position, in which the adjacent surfaces abut each other.

21. (Original) The mirror unit according to claim 20, wherein the mirror housing substantially extends along a motor vehicle in a folded orientation and the mirror housing is substantially oriented transversely to said motor vehicle in an unfolded orientation.

22. (Original) The mirror unit according to claim 20, wherein the actuator is configured to adjust the mirror unit in the unfolded orientation between the first position and the second position, such that during adjustment between the folded and the unfolded orientation the mirror unit is substantially in the first position.

23. (Original) The mirror unit according to claim 20, wherein the mirror foot includes a base pivot that pivotally engages the mirror housing.

24. (Withdrawn) The mirror unit according to claim 23, wherein the adjacent surfaces of the mirror housing and the mirror foot each form contact surfaces around the base pivot at a first distance, and wherein the mirror foot and the mirror housing cooperate via at least one cam path assembly curvedly extending around the base pivot at a second, smaller distance.

25. (Withdrawn) The mirror unit according to claim 24, wherein the at least one cam path assembly comprises a cam on one of the mirror housing or the mirror foot and a cam path provided on the other for engaging the cam, wherein the cam path includes a flat path part that forms the slit between the contact surfaces.

26. (Withdrawn) The mirror unit according to claim 25, wherein the flat path part allows the contact surfaces to adjust between the first and the second position.

27. (Original) The mirror unit according to claim 20, wherein said actuator is a linear actuator that adjusts the mirror foot and the mirror housing between the first position and the second position in a transverse direction with respect to a motor vehicle.

28. (Previously presented) The mirror unit according to claim 27, wherein at least a portion of one of the contact surfaces of the mirror foot or the mirror housing is comprised of an elastically deformable material.

29. (New) The mirror unit according to claim 8, wherein the pivot for the folded and unfolded orientations is provided within the mirror housing.